Bobcat™ 230 (Gas) See literature ED/4.45

Reliable, simple engine-driven welders great for stick and flux-cored welding. Designed for maintenance/repair operations, construction, farm, ranch and auxiliary power use.

Bobcat™ 230 3 Phase (Gas) See literature ED/4.47

For farm and ranch owners in need of single- and three-phase power. Designed to run 480-volt three-phase pivot irrigation systems and other farm/ranch equipment.

Bobcat™ 265 (Gas or LP) See literature ED/4.46

MOST POPULAR! **Reliable, easy to use and more capable engine-driven welders great for stick and flux-cored welding. Designed for maintenance/repair operations, construction, and auxiliary power use.**

Bobcat™ 265X (Gas) See literature EDX/4.46

Reliable, simple engine-driven welders great for stick and flux-cored welding. Designed for maintenance/repair operations, construction, farm, ranch and auxiliary power use.

**Electric fuel pump recommended for operation at altitudes above 1524 m (5,000 feet). This feature is on Bobcat 265 model 907826002 and sold as a kit for other Bobcat gas models (see accessories at right).*
***For LP model order Hose and LP Tank Mounting Assembly (301710) separately.*

Industrial ● CC CV DC

Processes

- Stick (SMAW) • MIG (GMAW)[1]
- Flux-cored (FCAW)[1] • DC TIG (GTAW)[2]
- Air carbon arc cutting and gouging (CAC-A)[3] (rated 4.8 mm [3/16 in.] carbons)

[1] *With voltage-sensing feeder.*
[2] *Bobcat 265 models only. Two-piece TIG torch recommended.*
[3] *Bobcat 265 models only.*

Engines

Gas: Kohler CH730 (with eChoke™ on Bobcat 265)
23.5 hp at 3,600 rpm
LP: Kohler CH730
Liquid withdrawal LP system
21 hp at 3,600 rpm
V-twin-cylinder, four-cycle, overhead valve, industrial, air-cooled

Note: Engines are warrantied separately by engine manufacturer.

Most popular accessories

- ArcReach® SuitCase® Feeders
- Spoolmate™ 200 300497 (Bobcat 265 only)
- Spoolmatic® 130831 (Bobcat 265 only)
- ArcReach® Stick/TIG Remote (Bobcat 265 ArcReach model only)
- Spectrum® 625 X-TREME™
- Running Gear
- Protective Cage with Cable Holders
- Hose and LP Tank Mounting Assembly
- Full KVA Adapter Cord 300517
- Protective Cover
- Remote Output Panel Kit 951850
- HWY-Mid Frame Trailer
- Remote Start/Stop Fob Replacement 286385
- Electric Fuel Pump Kit 301741 (gas models only, recommended for operation at altitudes above 1524 m [5,000 ft.])
- 7.6 m (25 ft.) Battery Charge/Jump Cables with Plug 300422 (for use with Bobcat 265 model with battery charge/crank assist)
- Spark Arrestor Kit 300924
- Screen Protector Kit 301742
- Sun Shade 301714

	Model	Stock Number*	Welding Mode	Welding Process	Amp/Volt Ranges	Rated Output at 40°C (104°F)	Auxiliary Power at 40°C (104°F)	Dimensions	Net Weight
Gasoline	Bobcat 230	**Non-remote start/stop model** **907824** Kohler with GFCI	CC/DC	Stick	20–230 A	230 A at 29.2 V, 100% duty cycle	Single-phase Peak: 11,000 watts Continuous: 9,500 watts	H: 673 mm (26.5 in.) H: 792 mm (31.2 in.) to top of exhaust W: 511 mm (20.13 in.) D: 941 mm (37.06 in.)	171 kg (376 lb.)
			CV/DC	MIG/FCAW	14–25 V	230 A at 25.5 V, 100% duty cycle			
	Bobcat 230 3 Phase	**Non-remote start/stop model** **907842** Kohler with GFCI	CC/DC	Stick	20–230 A	230 A at 29.2 V, 100% duty cycle	Single-phase/three-phase Peak: 10,000 watts Continuous: 8,500 watts		175 kg (385 lb.)
			CV/DC	MIG/FCAW	14–25 V	230 A at 25.5 V, 100% duty cycle			
Gas or LP	Bobcat 265	**907826** Kohler **907826001** Kohler with GFCI and ArcReach® **907826002** Kohler with GFCI and battery charge/crank assist **907826003** Kohler with GFCI and electric fuel pump **Non-remote start/stop model** **907827**** **LP** Kohler with GFCI	CC/DC	Stick/TIG	20–265 A	265 A at 27 V, 100% duty cycle	Single-phase Peak: 11,000 watts Continuous: 9,500 watts	H: 673 mm (26.5 in.) H: 792 mm (31.2 in.) to top of exhaust W: 511 mm (20.13 in.) D: 941 mm (37.06 in.)	Gas: 173 kg (382 lb.) LP: 166 kg (366 lb.)
			CV/DC	MIG/FCAW	14–30 V	265 A at 27 V, 100% duty cycle			
	Bobcat 265X	**907825** Kohler with GFCI							Gas: 171 kg (376 lb.)