# PIPE CRADLES & SLINGS

TAG Pipe Cradles and Slings are an effective way to move pipe, specifically designed for pipeline installation projects. TAG currently offers cradles from 2 - 24" and all are equipped with 4 inch urethane “round cut” wheels with sealed anti-friction bearings. All spreader bar designs are third party tested any comply with industry standards. These models are equipped with ⅝ wire rope and all rope is swedged and certified at a wire rope rigging company partnered with TAG.

## Features and Advantages

- Durable 90a urethane coating designed for multiple uses
- Sealed anti-friction bearings
- Measures 4" tread width x 4.5" diameter
- Designed for use with ⅝ wire rope
- Machined hub for smooth wheel rotation

| PART NO. | DESCRIPTION | LOAD CAPACITY (KG / LBS) |
|---|---|---|
| T2001 | Roller Sling 2 - 8" | 1,300kg / 3,000lbs |
| T2002 | 2 Strand Roller Cradle 6 - 12" | 7,710kg / 17,000lbs |
| T2003 | 2 Strand Roller Cradle 12 - 24" | 7,710kg / 17,000lbs |
| T2004 | 4 Strand Roller Cradle 12 - 24" | 12,700kg / 28,000lbs |

T2001

T2002

T2003

T2004

# ROLLER STANDS

*Light duty low level roller stands for pipe feeding*

## Features and Advantages

- Extremely easy pipe feeding
- Free standing or In-trench options
- Differing trench widths accommodated
- Multi positional
- Rubber coated rollers minimise pipe damage
- Three sizes available to suit pipes from 63 - 1200mm (2 - 48")

PRS3

PRS1

| PART NO. | PIPE DIAMETER RANGE (MM / INCH) | LOAD CAPACITY (KG / LBS) | WEIGHT (KG / LBS) |
|---|---|---|---|
| PRS1 | 63 - 355mm / 2 - 14" | 200kg / 440lbs | 5kg / 11lbs |
| PRS2 | 250 - 630mm / 10 - 24" | 1000kg / 2200lbs | 12kg / 27lbs |
| PRS3 | 500 - 1200mm / 20 - 48" | 1000kg / 2200lbs | 13kg / 29lbs |
| PRT1 | 63 - 355mm / 2 - 14" | 200kg / 440lbs | 6kg / 13lbs |

PRT1 - Pipe Roller for trenches