

TAG FLANGE PINS

Flange Pins are an economical and efficient way to align flanges. For use in $\frac{1}{2}$ - $1\frac{1}{2}$ " holes. Quick release design for fast flange alignment. Durable zinc coating finish increases tool life. For use in flange holes up to $1\frac{1}{2}$ " deep. Knurled handles increase grip. Lightweight 1.60kg / 3.5lbs.

PART NO.	SIZE (INCH)	DESCRIPTION
TQFFP1	$\frac{7}{16}$ - $1\frac{1}{2}$ "	Quick Fit Carbon Flange Pins
TFPSS1	$\frac{1}{4}$ - $\frac{7}{8}$ "	Stainless Steel Flange Pins



TAG MAGNETIC UNIVERSAL LEVEL

Designed primarily for pipe fitting applications. For all metal work the magnetic feature will offer an extra hand. Multi purpose tool offers 360 degree adjustable dial set level. Includes 2 x 20 pound magnets exerting 50 pound pull this will secure the unit in place on any steel, this enables hands free levelling. For aligning flanges the TAG Magnetic Universal Level is designed to be used with the Quick Flange Pins.

PART NO.	DESCRIPTION
TMUL	2 x 20lbs magnets



TAG CENTERING HEAD

The TAG Centering Head aids in the setting of centre lines, establishing angles and marks, for butt-ins, locating points inside pipes and tanks, laying out keyways and measuring declivity. Standard model is used on pipe $\frac{1}{2}$ " diameter and larger and has a 4" Y-type head fitted with an adjustable dial set level (DSL) and a manually operated hardened centering pin. The large centering head is ideal for pipe 1" diameter and up and has an 8" Y-type head and a DSL. A spring-loaded hardened centering pin eliminates the need for a hammer.

PART NO.	SIZE (INCH)
TCH	Standard $\frac{1}{2}$ " plus
TCHL	Extra Large 1" plus

